



MIGHTY EX9

Refrigeration Body

Engine			
Туре		Turbo Charger Intercooler	
		4 stroke-cycle, Water-cooled, Direct-inje	ction diesel Engine
Number of Cylinder		4 in-line 3.933cc	
Piston Displacement (cc)		Manual (5 Speed)	Auto (6 Speed)
Max. Power** ps/rpm (kw)	Euro V	170HP/2,500 (125kw) Man	170HP/2,500 (125kw) Man
Max. Torque ** (Nm/rpm)	Euro V	448/1,400 (608nm) Man	448/1,400 (608nm) Man
Fuel System	Injection pump	Denso Common Rail System	
Transmission	_		
Туре		Manual (6 Speed)	Auto (6 Speed)
Version		T060 S 6	Allison 1000x fe
Drive		Single Plate Clutch	Lock up Torque Converter
Park Pawl PTO		N/A Proporation for PTO	YES Preperation for PTO
Permissable Torque		Preperation for PTO 147 nm 2000 Rpm	339 nm (min rpm 1200)
Front Axle		117 1111 2000 11,011	(111111)
Туре		Reverse Elliot type " I " beam	
Capacity	kg	3100 kg	
Rear Axle		(400 kg	
Capacity	kg	6400 kg	
Tyre & Wheel Type		Single Front, Dual Rear	
Tyre	Front / Rear	215/75R17.5-12PR	
Wheel	Front / Rear	17.5 x 6.00	
Steering			
Steering		Power Assisted	
		Adjustable Steering Wheel	
Service Brake		Dice/Dice	
Front / Rear Vehicle Dynamic Control (VDC)		Disc/Disc (ESC) Electronic Stability Control, (ABS) Anti Brake Skid, (HSA) Hill Start Assist,	
verliele Dynamie control (vbc)		(ESS) Emergency Stop Signal	and Brake Skid, (1157) Till Start 715315t,
Parking Brake		()	
Actuation		Internal expanding type on Propeller sha	ft at the rear of Transmission assembly
Exhaust Brake			
Type		Vacuum operated, Butterfly Valve type	
Suspension Type	Front / Rear	Semi-elliptic, laminated Leaf Springs	
Shock absorber	HOIII / Real	Gas telescopic type on the FRONT/REAR	axle
Exhaust system			
General		Horizontal	
Fuel tank			
Capacity		100ℓ	
Frame		"H" type frame with channel sectional size	de rail & cross members, side rail is reinforced wi
Type Main section side rail dimension (mm)		Depth x Flange x Thickness : 183 x 60 x 6t	
Weights	()	4, 3	
*Chassis cab weight kg	Range	4600 kg	
** Max Gross Vehicle Weight		8,500 kg	
Gross vehicle weight	Front /Rear	3,100 kg/6,400 kg	
Box Body		Danal Lines Tuff (anti-maioture)	
Туре		Panel Liner Tuff (anti-moisture)	
Panel			de to 100T), 2x rows Internal F track preparation
Spec		=	Alloy chequer floor , Drain channel at front
Rear Door		Dual Container style Rear Doors, (optional	al upgrade to Triple Doors)
Side Door		LH Side Container Door (width approx 9	00mm) with folding step
Size m	MWB (3400)	Internal L 4.300, X W 2.2,x H 2.1 (optiona	l custom sizing available)
SIZCIII	. ,		-
	LWB (3850)	Internal L 4.850, X W 2.2,x H 2.1 (optiona	il custom sizing available)
Rear Bumper		Intergrated bumber step	
Refridgeration		Off engine refrigeration is included (city r	max 400 or similar), this is not installed until
		the point of sale, so optional upgrades to	plug in back up, freezer or choices from Carrier
		or Thermoking are possible	

Electrical system			
Audio	M450 (Radio+Aux/MP3 USB) Multidisplay		
Auto Locking	Central Door Locking + Power Window + Keyless Entry + Semi Trim		
Steering Wheel Controls	Bluetooth Phone - Audio - Cruise Control		
Head lamps	Semi-sealed Beam / Adjustable Dim		
Front Combination Lamps	Turn signal / Hazard-Amber, Position - White		
Fog Lamps	White		
Rear Combination lamps	Turn signal / Hazard-Amber, Tail / Stop - Red		
License Plate Lamp	White		
Service Lamp Circuit	Yes		
Daytime Running Lights	Yes		
12v Socket in Dash	Yes x2		
Power Windows	Yes		
Back-up Lamp	White		
Instruments			
Meter Cluster	Fixed type		
Meter	Speedometer / Tachometer / Fuel gauge / Water temperature gauge LCD with odometer / Trip meter / Clock		
Warning Lamps & Indicators	Brake fluid level of reservoir / Parking brake / Oil pressure / Battery charge /		
	Tell-tale lights for head light high beam / Turn signals / Door open / Seat belt / Low fuel		
Horn	Single, Electric		
Cruise Control	Yes		
Heating/ Air conditioning (Manual)	Yes		
Steering Wheel Audio Remote Control	Yes		
Steering Wheel Auto Cruise Control	Yes		
Body /Cab			
Type Mounting	Tilt type with torsion bars, all steel welded construction with safety zone design Rigid or Semi floating type		
Windshield	One piece type with laminated glass, tinted upper section		
Windshield Wipers	Dual electric three speed (intermittent / low / fast) wipers & washer		
Mirrors	Mirror - Heated		
Driver's Seat	Coil Suspension, urethane foam cushioned STD trim		
Passenger's seat	Bench seat, STD Trim		
Steering Column	Fully Adjustable		
Roof Marker Lights	Yes		
Overhead Storage	Yes		
Mirror Width	Narrow STD (optional LONG)		
Active Safety Feautures	Yes		
Electronic Stability Control	Yes		
ABS Braking	Yes		
Daytime Running Lights Hill Start Assist	Yes		
Auto Headlights	Yes		
Bluetooth Hands Free	Yes		
Heated Mirrors	Yes		
Warranty	Tes		
Cab Chassis	3 years or 150,000km (whichever occurs first) against manufactures defects		
Upper body	According to supplier		
Refrigeration	Where applicable Any refrigeration supplied will be either from Transcold or Thermo king, all warranty and service		
	be according to their terms and conditions		
Annotations			

1) Empty vehicle weight and curb weight shown are to 3.5% variation to allow for production tolerance.

2) Empty vehicle weight and curb weight include weight of oil, fuel, coolant and spare tire carrier & bracket, but exclude standard tool set

3) The vehicle specification may differ per country.

4) Hyundai New Zealand reservs the right to alter the specifications, equipment or options or discontinue the models at any time without prior notice.


*Approximate, depending on variant and specification

 $^{**}\text{Max GVW includes the front and rear axle loads based on permissable tyre load 5,995kg \& 6,500kg varients}$

images may contain additional cost options

MIGHTY EX9

Refrigeration Body



Please Note:

- -All drawings are indicative and may show additional cost options
- -All measurements should be viewed as approximate measurements
- -Internal measurements shown are wall to wall or floor to ceiling, door entrances and floor may have a reduced measurement due to construction requirements
- -Refrigeration unit shown is for marketing purposes only (please refer page 2 refrigeration specification for detail)
- -Dimensions shown are a standard specification however build to order custom specifications are available on request